



New ENOC O5 FIBER OPTIC CABINET



Enoc O5 is a series of fiber optic cabinets in three widths. The cabinet is delivered complete with a ground anchor, lock and condensation protection for roof and ground. Enoc O5 is available in hot dip galvanized C3H or powder coated magnelis plate C5-I (RAL 7037). Snow post, sling holder and key are available as accessories. C5-M on request.

THREE SIZES:

Width: 330 mm, 390 mm and 600 mm
Height: 875 mm (above ground)
Depth: 207 mm

MATERIAL

Hot dip galvanized, ISO 1461
Powder coated magnelis plate,
RAL 7037



ENOCSYSTEM.COM

ENOC



TECHNICAL INFORMATION ENOC O5 FIBER OPTIC CABINET



FIBER OPTIC CABINET

- Complete Fiber Optic Cabinet (outdoor) for fiber installation.
- Anchoring plate
- Ground fixing. Dig down depth stepless up to 800 mm
- Condensation plate in the roof
- Ground insulation plate

NAME	ART. NO	EAN	E NO	WxDxH (mm)	YTB
O5 33-G	57801	7330701036507	5060148	330x207x1035	G
O5 33-P	57811	7330701036606	5060149	330x207x1035	P
O5 39-G	57802	7330701036514	5060150	390x207x1035	G
O5 39-P	57812	7330701036613	5060151	390x207x1035	P
O5 60-G	57803	7330701036521	5060152	600x207x1035	G
O5 60-P	57813	7330701036620	5060153	600x207x1035	P

G = Hot dip galvanized plate. C3H

P = Powder coated Magnelis plate. C5-I Medium

*Other locks on request

COLORS




Hot dip galvanized plate according to SS-EN ISO 1461 Corrosion class C3 High according to ISO 12944




Powder coated Magnelis plate (RAL 7037). Corrosion class C5-I Medium, according to ISO 12944.

ACCESSORIES




SLING HOLDER, SH O5
Width: 270 mm
Depth: 65 mm
Radius: 25 mm
Material: Magnelis plate



SNOW POST, SP O5
Including fasteners
Length: 1250 mm
Material: Aluminium
Color marking: Opto, green-white-green

KEY
KEY Stockholm



600 MM

390 MM

330 MM

NAME	ART. NO	EAN	E NO	DESCRIPTION
KEY STOCKHOLM	57831	7330701036804	5060154	Key
SP O5	57821	7330701036705	5060159	Sling holder
SH O5	57826	7330701036750	5060161	Snow post